

Schedule C – No. 2 Oil Specifications
Van Sant Generating Station
No. 2 Fuel Oil (< .3% Sulfur By Weight)
Specifications

Flash Point	130	degF
Water and Sediment	0 to .1	% by volume
Carbon Residue (10% Bottom)	.35	% max
Carbon Residue (100% Sample)	1.0	% max
Heating Value, Btu/lb gross (calculated)	19,170 to 19,750	
Gravity Deg API	28 to 40	
Specific Lb/gal	.887 to .825 7.39 to 6.87	
Sulfur	< 0.3	% by weight
Hydrogen	11.8 to 13.9	% by weight
Carbon	86.1 to 88.2	% by weight
Nitrogen	nil to .1	% by weight
Oxygen	N/A	% by weight
Ash	100	ppm max
Pour Point, F	10 to -40	
Viscosity:		
Centistokes at 100 F	1.9 to 3.6	
SUS at 100 F	32 to 38	

Supplier or Shipper will be provided 7 days per week/24 hours per day access to the facility for oil deliveries and no truck size limitations will be in effect at the loading facility. No more than 1 truck is capable of unloading at one time.

Shipper must provide a sample from the delivery to the plant operator for testing of sulfur content and shall not unload until completed test confirms that shipment meets specifications. In the event that the oil testing causes a material expense for CESI, the Parties will determine, on a mutually agreeable basis, a make whole provision which compensates accordingly CESI for such expense.